



FKSZ2.E337596 - Light-emitting-diode Drivers - Component

Light-emitting-diode Drivers - Component

See General Information for Light-emitting-diode Drivers - Component

GLACIALTECH INC

E337596

6th Fl 346 Sec 2 Jung Shan Rd
Jung He District
New Taipei, 235 TAIWAN

LED Driver, Class 2 output, Model(s) GP-HS15P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

LED Driver, isolated LPS output, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-12zzz #, GP-LP060P-24zzz #, GP-LP060P-28zzz #, GP-LP060P-36zzz #, GP-LP060P-48zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-50zzz #

LED Driver, isolated output, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-30XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@

LED Drivers Other Than Class 2, Model(s) GP-LC6672-32D, GP-LV6672-32D

LED Drivers, Isolated Class 2 Output, Model(s) GP-HS60P-24C1zzz(\$), GP-HS60P-24CA1zzz(\$), GP-HSwwP-xxCyzzz(*), GP-HSwwP-xxCyzzz(**), GP-LCA048-32D, GP-LCA336-32D, GP-LCB024-32D, GP-LVA048-32D, GP-LVA336-32D, GP-LVB024-32D, GP-RSwwP-xxCyzzz(*), GP-RSwwP-xxCyzzz(**), GP-TL3536-26, GP-TL7018-26, GP-TL7512-27, GP-TL3724-27, GP-TL2536-27, GP-TLA012-26, GP-TLA014-26

LED drivers, isolated output, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-42XYZ@, GP-LS150P-48XYZ@

Model. No.	Input						Output					Env. Loc.	Type HL	Type TL	Tref max (°C)	Wired Tref Control (°C)	Phase cut Diming
	Supply Conn. Method	Volts (V)	Freq (Hz)	Power (W)	Amps (A)	Type	Volts (V)	Freq (Hz)	Power (W)	Amps (A)	Type [a]						
GP-CVM100P-12VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	1.5	Non-isolated	12Vdc	-	99.6	8.3	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM100P-24VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	1.5	Non-isolated	24Vdc	-	100.8	4.2	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM100P-36VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	1.5	Non-isolated	36Vdc	-	100.8	2.8	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM100P-48VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	1.5	Non-isolated	48Vdc	-	100.8	2.1	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM200P-12VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	3.15	Non-isolated	12Vdc	-	200.4	16.7	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM200P-24VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	
	Leads	100-277Vac	50/60	-	3.15	Non-isolated	24Vdc	-	199.2	8.3	CV, Isolated	Wet	-	-	-	b	a a
GP-CVM200P-36VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.																	

	Leads	100-277Vac	50/60	-	3.15	Non-isolated	36Vdc	-	198	5.5	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM200P-48VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	3.15	Non-isolated	48Vdc	-	199.2	4.15	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM300P-12VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	5	Non-isolated	12Vdc	-	249.6	20.8	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM300P-24VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	5	Non-isolated	24Vdc	-	300	12.5	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM300P-36VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	5	Non-isolated	36Vdc	-	298.8	8.3	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM300P-48VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	5	Non-isolated	48Vdc	-	300	6.25	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM400P-12VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	6.3	Non-isolated	12Vdc	-	320.4	26.7	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM400P-24VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	6.3	Non-isolated	24Vdc	-	400.8	16.7	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM400P-36VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	6.3	Non-isolated	36Vdc	-	399.6	11.1	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVM400P-48VyZZZ where xx = 12, 24, 36 or 48 means the output voltage rating in unit Vdc where y can be blank, A or D, blank means non-dimmable, A means dimming function with 3 in 1, D means dimming function with DALI where ZZZ can be any alphanumeric character or blank for marketing purposes only.</p>																			
	Leads	100-277Vac	50/60	-	6.3	Non-isolated	48Vdc	-	398.4	8.3	CV, Isolated	Wet	-	-	-	-	b	a	a
<p>GP-CVP040N-12VL-P02 indicates the output wattage which to 040 in unit W. Where xx indicates the output voltage which may be 12 or 24 in unit Vdc</p>																			
	Leads	120Vac	50/60	-	0.67	Non-isolated	12Vdc	-	40	3.4	CV, Class 2	Damp	-	-	-	-	a	a	b
<p>GP-CVP040N-24VL-P02 indicates the output wattage which to 040 in unit W. Where xx indicates the output voltage which may be 12 or 24 in unit Vdc.</p>																			
	Leads	120Vac	50/60	-	0.67	Non-isolated	24Vdc	-	40	1.7	CV, Class 2	Damp	-	-	-	-	a	a	b
<p>GP-CVP075N-24VL-P02 indicates the output wattage which to 075 in unit W. Where xx indicates the output voltage which may be 24 in unit Vdc</p>																			
	Leads	120Vac	50/60	-	0.95	Non-isolated	24Vdc	-	75	3.2	CV, Class 2	Damp	-	-	-	-	a	a	b
<p>GP-HS10P-12C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.</p>																			
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a

GP-HS10P-24C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS10P-36C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS10P-48C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS10P-52C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-12C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-12V(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-22C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-24V(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-30C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-36V(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-42C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-48V(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-52C(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS15P-52V(X) , (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS25P-(X)(Y) , (X) may be 48 or 52 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations.																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-HS25P-(X)(Y) , may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations																				
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LE036N-12CZZZ zzz can be any alphanumeric character or blank																				
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	9-12Vdc	-	33.6	2.8	CC, Class 2	Dry	-	-	-	-	+	-	-	
GP-LE036N-12VZZZ zzz can be any alphanumeric character or blank																				
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	12Vdc	-	36	3.0	CV, Class 2	Dry	-	-	-	-	+	-	-	
GP-LE036N-15VZZZ zzz can be any alphanumeric character or blank																				
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	15Vdc	-	36	2.4	CV, Class 2	Dry	-	-	-	-	+	-	-	
GP-LE036N-18VZZZ zzz can be any alphanumeric character or blank																				
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	18Vdc	-	36	2.0	CV, Class 2	Dry	-	-	-	-	+	-	-	
GP-LE036N-24CZZZ zzz can be any alphanumeric character or blank																				

	Leads	100-277Vac	50/60	-	1.0	Non-isolated	16-24Vdc	-	33.6	1.4	CC, Class 2	Dry	-	-	-	-	+	-	-
GP-LE036N-24VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	24Vdc	-	36	1.5	CV, Class 2	Dry	-	-	-	-	+	-	-
GP-LE036N-36CZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	24-36Vdc	-	37.8	1.05	CC, Class 2	Dry	-	-	-	-	+	-	-
GP-LE036N-36VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	36Vdc	-	36	1.0	CV, Class 2	Dry	-	-	-	-	+	-	-
GP-LE036N-48CZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	36-48Vdc	-	33.6	0.7	CC, Class 2	Dry	-	-	-	-	+	-	-
GP-LE036N-48VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	1.0	Non-isolated	36Vdc	-	48	0.75	CV, Class 2	Dry	-	-	-	-	+	-	-
GP-LE060N-12VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	-	Non-isolated	12Vdc	-	-	-	CC, Class 2	Damp	-	-	-	-	+	-	-
GP-LE100N-12VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	2	Non-isolated	12Vdc	-	102	8.5	CC, Isolated	Damp	-	-	-	-	+	-	-
GP-LE100N-24VZZZ zzz can be any alphanumeric character or blank																			
	Leads	100-277Vac	50/60	-	2	Non-isolated	24Vdc	-	100.8	4.2	CC, Isolated	Damp	-	-	-	-	+	-	-
GP-LS100PH-142C1xyy%	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS100PH-142Cxyy%	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS100PH-71Cxyy%	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS120PH-XXXYYZZZ , where XXX = 227 or 343, VVV = 099, 107, 113, 143, 210, 284 or 428, Y = D (dimming function), A (adjustable function), T (timing function) or blank, Z = 0~9, A~Z or blank.																			
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS150PH-VVYYZZZ , where XXX = 227 or 343, VVV = 099, 107, 113, 143, 210, 284 or 428, Y = D (dimming function), A (adjustable function), T (timing function) or blank, Z = 0~9, A~Z or blank.																			
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS50PH-142Cxyy%	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a
GP-LS70PH-100Cxyy%	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	+	a	a

[a] Identifies if the product itself has isolation between input and output based on the requirements of the standard. Output type (Non-isolated, Isolated, Class 2, LED Class 2) is designated based on the requirements that have been applied.

Wired Control Circuit: a = This device does not have a wired control circuit, b = This device has a wired control circuit that is isolated per Supplement SF, c = This device has a wired control circuit that is nonisolated per Supplement SF, + = Not evaluated

Phase-cut Dimming: a = This device has not been evaluated per Supplement SH, b = This device has been evaluated per Supplement SH, c = This device has been evaluated per Supplement SH for use with specific dimmer models - see UL Report.

- zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.


(\$\$) - zzz may be A through Z, 0 through 9 or blank for marketing purpose only

(*) - ww may be 45 or 60; xx may be 12, 24, 36, 42, 48 or 57; y may be A or blank for dimming designation, A means dimmable, blank means non-dimmable; zzz may be A through Z, 0 through 9 or blank for marketing purpose only.

(**) - ww may be 35 or 26; xx may be 12, 24, 36, 42, 48 or 57; y may be A or blank for dimming designation, A means dimmable, blank means non-dimmable; zzz may be A through Z, 0 through 9 or blank for marketing purpose only

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only

Marking: Company name, model designation, and the Recognized Component Mark,  .

Last Updated on 2020-07-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"