



## FKSZ2.E337596

## Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

[Page Bottom](#)

## Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

[See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component](#)**GLACIALTECH INC**

E337596

9TH FL  
 352 SEC 2 JUNG SHAN RD  
 JUNG HE  
 TAIPEI HSIEN, 235 TAIWAN

**LED Driver, Class 2 output**, Model(s) GP-HS10P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-24C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-48C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-22C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-24V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-30C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-42C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-48V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-52V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS25P-(X)(Y), (X) may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations

GP-HS25P-(X)(Y), (X) may be 48 or 52 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations.

**LED Driver, isolated LPS output**, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-12zzz #, GP-LP060P-24zzz #, GP-LP060P-28zzz #, GP-LP060P-36zzz #, GP-LP060P-48zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-50zzz #

**LED Driver, isolated output**, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-30XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@

**LED Drivers, Isolated Limited Output**, Model(s) GP-LS50PH-142Cxyy%, GP-LS70PH-100Cxyy%, GP-LS100PH-71Cxyy%, GP-LS100PH-142Cxyy%, GP-LS100PH-142C1xyy%.


**LED drivers, isolated output**, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-48XYZ@

# - zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only

Marking: Company name, model designation, and Recognized Component Mark,  .  
Last Updated on 2012-08-20

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

? 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".



## FKSZ8.E337596

## Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

[Page Bottom](#)Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for **Canada** - Component[See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component](#)**GLACIALTECH INC**

E337596

9TH FL  
352 SEC 2 JUNG SHAN RD  
JUNG HE  
TAIPEI HSIEN, 235 TAIWAN

**LED Driver, Class 2 output**, Model(s) GP-HS10P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-24C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-22C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-24V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-30C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS25P-(X)(Y), (X) may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations

**LED Driver, isolated LPS output**, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-12zzz #, GP-LP060P-24zzz #, GP-LP060P-28zzz #, GP-LP060P-36zzz #, GP-LP060P-48zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-50zzz #

**LED Driver, isolated output**, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-30XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@

**LED Drivers, Isolated Limited Output**, Model(s) GP-LS50PH-142Cxyy%, GP-LS70PH-100Cxyy%, GP-LS100PH-71Cxyy%, GP-LS100PH-142Cxyy%, GP-LS100PH-142C1xyy%.

**LED drivers, isolated output**, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-48XYZ@

# - zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only



Marking: Company name, model designation and Recognized Component Mark for Canada,

[Last Updated](#) on 2012-08-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

? 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".