UL ONLINE CERTIFICATIONS DIRECTORY

FKSZ2.E337596
Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component
Page Bottom

Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

GLACIALTECH INC E337596
9TH FL
352 SEC 2 JUNG SHAN RD
JUNG HE
NEW TAIPEI, 235 TAIWAN

LED Driver, Class 2 output, Model(s) GP-HS10P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-24C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-48C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-22C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-24V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-30C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-42C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-48V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-52V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS25P-(X)(Y), (X) may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations

GP-HS25P-(X)(Y), (X) may be 48 or 52 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations.

LED Driver, isolated LPS output, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-12zzz #, GP-LP060P-24zzz #, GP-LP060P-28zzz #, GP-LP060P-36zzz #, GP-LP060P-48zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-50zzz #

LED Driver, isolated output, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-30XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@

LED Drivers, Isolated Limited Output, Model(s) GP-LS50PH-142Cxyy%, GP-LS70PH-100Cxyy%, GP-LS100PH-71Cxyy%, GP-LS100PH-142Cxyy%, GP-LS100PH-142C1xyy%.

LED drivers, isolated output, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-42XYZ@, GP-LS150P-48XYZ@

- zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only

Marking: Company name, model designation, and Recognized Component Mark, .
Last Updated on 2013-03-04