



Product Service

CERTIFICATE

No. B 07 08 64337 001

Holder of Certificate: GlacialPower Inc.

5 F, No. 350, Sec. 2, Jung Shan Road
235 Jung He City, Taipei,
TAIWAN

Certification Mark:



Product: Power supplies

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.: 612107120601

Date, 2007-08-24

Page 1 of 3

Bill





CERTIFICATE
No. B 07 08 64337 001

Model(s): GP-SLxxxxyyy
 ("xxx" can be 200, 235, 250, 300, 350, 400, 450
 or 500 to denote the different output power wattage;
 "yyy" can be 0-9, A-Z or blank to denote the different
 client ID.)

Parameters:

Rated input voltage:	115/230 Vac
Rated input current:	See attachment
Rated frequency:	60/50 Hz
Rated outputs:	See attachment
Protection class:	I
Max. ambient temperature:	40°C
Degree of protection against ingress of liquids:	Ordinary

Remark: When installing, all requirements of below
 mentioned test standards must be fulfilled.

Tested according to: EN 60950-1/A11:2004

Production Facility(ies): 50076

Main-Certificate no.: B 06 07 50034 038

Bill



Taiwan

Attachment to the Certificate

No. B 07 08 64337 001

The ratings & model description of the models are as below:

Model-#	AC Input Ratings	DC Output Ratings						Max. Wattage
		+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb	
GP-SL200yyyy	115/230 Vac, 60/50 Hz, 6/4 A	10 A	6 A	6 A	9 A	0.3 A	2.5 A	200 W
		(+3.3V and +5V total power max. 63 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 185 W)						
GP-SL235yyyy	115/230 Vac, 60/50 Hz, 6/4 A	12 A	8 A	6 A	10 A	0.3 A	2.5 A	235W
		(+3.3V and +5V total power max. 79 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 220 W)						
GP-SL250yyyy	115/230 Vac, 60/50 Hz, 6/4 A	14 A	12 A	8 A	13 A	0.3 A	2.5 A	250 W
		(+3.3V and +5V total power max. 106 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 235 W)						
GP-SL300yyyy	115/230 Vac, 60/50 Hz, 8/4 A	18 A	12 A	8 A	13 A	0.3 A	2.5 A	300 W
		(+3.3V and +5V total power max. 119 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 285 W)						
GP-SL350yyyy	115/230 Vac, 60/50 Hz, 8/4 A	20 A	12 A	10 A	13 A	0.3 A	2.5 A	350 W
		(+3.3V and +5V total power max. 126 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 335 W)						
GP-SL400yyyy	115/230 Vac, 60/50 Hz, 10/6 A	20 A	14 A	14 A	13 A	0.3 A	2.5 A	400 W
		(+3.3V and +5V total power max. 130 W) (+3.3V, +5V, +12V1 and +12V2 total power max.385 W)						
GP-SL450yyyy	115/230 Vac, 60/50 Hz, 10/6 A	22 A	15 A	14 A	16 A	0.3 A	2.5 A	450 W
		(+3.3V and +5V total power max. 130W) (+3.3V, +5V, +12V1 and +12V2 total power max. 435 W)						
GP-SL500yyyy	115/230 Vac, 60/50 Hz, 10/6 A	22 A	16 A	15 A	16 A	0.8 A	2.5 A	500 W
		(+3.3V and +5V total power max. 130 W) (+3.3V, +5V, +12V1 and +12V2 total power max. 480 W)						

Date: 2007-08-24



Testing Laboratory

Bill Lin

Bill Lin