


Model: GP-LS070P Series

Features

- Universal AC Input 100~277VAC.
- Constant Voltage / Constant Current Operation.
- Suitable for LED Lighting Applications.
- Built-in PFC Function.
- Protections: OCP / SCP / OTP.
- IP67 Level Design for Indoor or Outdoor Installations.
- Cooling by Free Air Convection.

Approvals

CE FC cUL[®]us IP67



Size

176 * 68 * 39 mm (L*W*H)





Specifications

Model No.		GP-LS070P-12	GP-LS070P-24(30V)	GP-LS070P-36	GP-LS070P-48(54V)
Output	DC Voltage Range Note.2	10~12V	18~24V(20~30V)	25~36V	33~48V(37~54V)
	Rated Current	4.9A	3.2A(2.45A)	2.1A	1.4A
	Current Tolerance	±5%	±5%	±5%	±5%
	Rated Power	59W	75W(73.5W)	75.6W	67W(75W)
	Ripple & Noise (Max.) Note.3	2.5V	3V	4V	4V
	Efficiency at 230VAC (Typ.)	86%	86%	86%	86%
	Voltage Tolerance Note.4	5%	5%	5%	5%
Input	Voltage Range	90 ~ 305VAC / 127 ~ 373VDC			
	Frequency Range	47 Hz ~ 63 Hz			
	AC Current (Max.)	2A at 115VAC / 1A at 230VAC			
	Power Factor	>0.98 at 115VAC / ≥0.94 at 230VAC at full load. ≥0.9 at 70% load.			
	Inrush Current (Max.)	65A at 230VAC (COLD STAR)			
	Leakage Current	<0.5mA / 240VAC			
Protections	Over Current	5~108% rated current. Type: Constant current limit and recovers after fault condition disappeared.			
	Short Circuit	Type: Hiccup mode & recovers after fault condition disappeared.			
	Over Temperature	Tcase: 95°C ±10°C Type: Hiccup mode & recovers after fault condition disappeared.			
Environment	Operation Temp.	-20 ~ 50°C at Full Load, 70°C at 60% Load (Refer to output load derating curve)			
	Operation Humidity	20% ~ 90% RH non-condensing.			
	Storage Temp.	-40 ~ +80°C			
	Storage Humidity	10% ~ 90% RH			
	Vibration	10~500 Hz, 2G 10 min./1 cycle, period for 60 min. each along X, Y, Z axes.			

Safety & EMC	Safety Standards	UL8750,,EN61347-1,EN61347-2-13 ,IP67
	Withstand Voltage	I/P-O/P: 3.75KVAC I/P-FG:1.88KVAC O/P-FG:0.5KVAC
	Isolation Resistance	I/P - O/P, I/P - FG : 100M ohms / 500VDC at 25°C
	EMI Conduction & Radiation	Compliance to EN55015,FCC part 18
	Harmonic Current	Compliance to EN61000-3-2 Class C (≥ 75% Load),EN61000-3-3
	EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11 Light industry level, criteria A
Others	MTBF	300K hours min.MIL-HDBK-217F(25°C)
	Dimension(L x W x H)	176 x 68 x 39 mm; 816.4g/pcs
Note	1. All specifications not specially mentioned are measured at 230VAC and 25°C ambient temperature. 2. The range is for constant current application. 3. Ripple & Noise are measured at 20MHz bandwidth by using a 12" twisted pair-wire terminated with 0.1uf & 47uf parallel capacitor. 4. Voltage Tolerance: includes line regulation, load regulation and set-up tolerance.	

Derating Curve



Mechanical Specification

