

FKSZ2.E337596

Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component Page Bottom

Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

GLACIALTECH INC 9TH FL 352 SEC 2 JUNG SHAN RD JUNG HE TAIPEI HSIEN, 235 TAIWAN E337596

LED Driver, Class 2 output, Model(s) GP-HS10P-12C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS10P-24C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS10P-36C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS10P-48C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS10P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-12C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-12V(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-22C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-24V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-30C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-36C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-36V(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-42C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-48V(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-52C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS15P-52V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only. GP-HS25P-(X)(Y), (X) may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations

GP-HS25P-(X)(Y), (X) may be 48 or 52 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations.

LED Driver, **isolated LPS output**, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-12zzz #, GP-LP060P-24zzz #, GP-LP060P-28zzz #, GP-LP060P-28zzz #, GP-LP075P-15zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-16zzz #, GP-LP075P-16zzz #, GP-LP075P-16zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-28zzz #, GP-LP075P-28zz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zz #, GP-LP075P-28zz

LED Driver, **isolated output**, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-36XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@, GP-LS070P-36XYZ@, GP-LS070P-30XYZ@, GP-LS0

LED Drivers, Isolated Limited Output, Model(s) GP-LS50PH-142Cxyy%, GP-LS70PH-100Cxyy%, GP-LS100PH-71Cxyy%, GP-LS100PH-142Cxyy%, GP-LS100PH-142C1xyy%.

LED drivers, isolated output, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-48XYZ@, GP-LS150P

- zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only

Marking: Company name, model designation, and Recognized Component Mark, Park . <u>Last Updated</u> on 2012-08-20						
Questions?	Print this page	Terms of Use	Page Top			

? 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the <u>UL Environment database</u> for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".

ONLINE CERTIFICATIONS DIRECTORY

FKSZ8.E337596 Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

Page Bottom

Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

GLACIALTECH INC 9TH FL 352 SEC 2 JUNG SHAN RD JUNG HE TAIPEI HSIEN, 235 TAIWAN E337596

LED Driver, Class 2 output, Model(s) GP-HS10P-12C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-24C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS10P-36C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-12V(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-22C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-24V(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-30C(X),(X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36C(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS15P-36V(X), (X) = ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only.

GP-HS25P-(X)(Y), (X) may be 12, 18, 24 or 36 for output Voltage, (Y) = yyy and y may be may be A through Z, 0 through 9 or blank for customer code, Suitable for Dry locations

LED Driver, **isolated LPS output**, Model(s) GP-LP048P-28zzz #, GP-LP050P-12zzz #, GP-LP050P-24zzz #, GP-LP050P-36zzz #, GP-LP050P-48zzz #, GP-LP060P-28zzz #, GP-LP060P-28zzz #, GP-LP060P-28zzz #, GP-LP075P-15zzz #, GP-LP075P-15zzz #, GP-LP075P-15zzz #, GP-LP075P-16zzz #, GP-LP075P-18zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-36zzz #, GP-LP075P-48zzz #, GP-LP075P-19zzz #, GP-LP075P-19zzz #, GP-LP075P-20zzz #, GP-LP075P-24zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-48zzz #, GP-LP075P-20zzz #, GP-LP075P-20zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-48zzz #, GP-LP075P-20zzz #, GP-LP075P-20zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-28zzz #, GP-LP075P-48zzz #, GP-LP075P-28zzz #, GP-LP075P-28zz #, GP-LP075P-28zzz #, GP-LP075P-28zz #, GP-LP075P-28zzz #, GP-LP075P-28zz #,

LED Driver, **isolated output**, Model(s) GP-LS050P-12XYZ@, GP-LS050P-24XYZ@, GP-LS050P-36XYZ@, GP-LS050P-48XYZ@, GP-LS070P-12XYZ@, GP-LS070P-24XYZ@, GP-LS070P-36XYZ@, GP-LS070P-36XYZ@, GP-LS070P-48XYZ@, GP-LS070P-54XYZ@, GP-LS070P-36XYZ@, GP-LS070P-30XYZ@, GP-LS0

LED Drivers, Isolated Limited Output, Model(s) GP-LS50PH-142Cxyy%, GP-LS70PH-100Cxyy%, GP-LS100PH-71Cxyy%, GP-LS100PH-142Cxyy%, GP-LS100PH-142C1xyy%.

LED drivers, isolated output, Model(s) GP-LS100P-12XYZ@, GP-LS100P-24XYZ@, GP-LS100P-30XYZ@, GP-LS100P-36XYZ@, GP-LS100P-48XYZ@, GP-LS120P-48XYZ@, GP-LS150P-12XYZ@, GP-LS150P-24XYZ@, GP-LS150P-30XYZ@, GP-LS150P-36XYZ@, GP-LS150P-48XYZ@, GP-LS15

- zzz can be any alphanumeric or blank for marketing purpose only

% - x=blank without dimmer; x = A with dimmer; yy= any character or number or blank for marketing purpose only.

@ - XYZ may be any character or number or blank for marketing purposes only

X - ZZZ and Z may be A through Z, 0 through 9 or blank for marketing purpose only

Marking: Company name, model designation and Recognized Component Mark for Canada, C The Last Updated on 2012-08-20

Questions?	Print this page	Terms of Use	Page Top	
				? 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the <u>UL Environment database</u> for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".