

Model: GP-ES320P Series

320 Watts single output

Features:

- * 3.3V&5V use patented synchronous rectification
- * Ball-bearing fan speed control by thermal detection
- * Built-in constant current limiting design
- * Active PFC with P.F.>0.95
- * Full load operation from -20°C~50°C
- * Protections:Over load/Over voltage/Short circuit/Over temperature
- * High efficiency up to 89%
- * Universal AC input: 90~264Vac
- * Remote ON/OFF control(optional)

Size : 215 * 115 * 50 mm (L*W*H)



Specifications:

Approvals : CB CE  

Model No.		ES320P-3.3	ES320P-05	ES320P-12	ES320P-15	ES320P-24	ES320P-48
Output	DC Voltage	3.3V	5V	12V	15V	24V	48V
	Rated Current Range	0~55A	0~55A	0~25A	0~20A	0~13A	0~6.7A
	Rated Max. Power	181.5W	275W	300W	300W	312W	321.6W
	Ripple & Noise (max)	100mV	100mV	120mV	150mV	150mV	240mV
	Efficiency	77%	81%	86%	86%	87%	89%
	Voltage Adjustment Range	3.15~3.5V	4.5~5.5V	10~13V	13.5~17V	20~27V	41~52V
	Voltage Tolerance	±2%	±2%	±1%	±1%	±1%	±1%
	Rise Time	<50ms at full load					
Set up Time	1000ms/230vac 2500ms/115vac						
Hold Time	>16ms at full load						
Input	Voltage Range	90 Vac ~ 264 Vac or 127~370VDC					
	Frequency Range	47 Hz ~ 63 Hz					
	Power Factor Correction	> 0.95/230VAC 0.98/115VAC					
	AC Current	2.5A@115VAC / 1.3A@230VAC		4.5A@115VAC / 2.3A@230VAC			
	Inrush Current	20A at 115VAC / 40A at 230 VAC (COLD START)					
	Leakage Current	<1mA / 240 Vac					
Protections	Over Load	over 105~135% output rating and by constant current mode . recovers automatically after fault condition has been removed.					
	Over Temperature	key part detect over 85 °C± 5°Cand by shutdown output voltage, re-power on to restart					
	Short Circuit	by constant current mode . recovers automatically after fault condition has been removed.					
	Over Voltage	3.8~4.5V	5.75~6.75V	14~16V	17.3~21V	29~33.6V	57~67V
Function	Remote Control	CON2: 4~10VDC POWER OFF, 0~0.8VDC POWER ON					
Environment	Operation Temp.	-20°C~50°C full load , 50°C~65°C(Refer to output load derating curve)					
	Operation Humidity	20% ~ 90% RH non-condensing.					
	Storage Temp.	-40 ~ +80°C					
	Storage Humidity	10% ~ 90% RH					
	Vibration	10 ~ 500 Hz, 2G 10 min. / 1 cycle, 60 min. each along X, Y, Z axes.					
Safety & EMC	Safety Standards	UL60950-1, TUV EN60950-1 , Approved.					
	Withstand Voltage	I/P - O/P: 3 K VAC I/P - FG: 1.5KVAC O/P - FG: 0.5KVAC					
	Isolation Resistance	100M ohms / 500VDC at 25 °C : I/P-O/P, I/P-FG, O/P-FG					
	EMI Conduction&Radiation	Compliance to EN55022 class B, CISPR22 class B					
	Harmonic Current	Compliance to EN61000-3-2, -3					
Others	EMS Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11 Light industry level, criteria A					
	MTBF	210k hours min.MIL-HDBK-217F(25°C)					
	Dimension(L*W*H)	215*115*50mm					
	Packing(L*W*H)/Carton	492*258*201mm / 12 PCS					
Remark	Weight	1.1KG/PCS N.W: 14KG/Carton (12PCS)					
	1. All specification measured at 230 vac input and 25 °C ambient . 2. Ripple & noise are measured at 20MHz bandwidth oscilloscope and with 0.1uf & 47uf parallel capacitor. 3. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.						

